UNG HASTINU

COPY NO.

U·S·NAVAL·TECHNICAL·MISSION·IN·EUROPE

TECHNICAL REPORT No. 485-45

UNCLASSIFIED

GERMAN POWDER COMPOSITION AND INTERNAL BALLISTICS FOR GUNS

gira 9-11-3122

Copy available to DTIC does not permit fully legible reproduction

October 1945

THE FILE COPY

AD A 95313



J-S-NAVAL-TECHNICAL-MISSION-IN-EUROP

CONSTRE

This document has been approved for public release and sale; its distribution is unlimited.

and the said

11= 700/P 69

DISCLAIMER NOTICE

THIS DOCUMENT IS BEST QUALITY PRACTICABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

U. S. NAVAL TECHNICAL MISSION IN EUROPE c/o Floot Post Office New York, N.Y.

File: 19-16(3)(40/Hn)

Serial: 01353

26 October 1945

From: Chief, U.S. Naval Tochnical Mission in Europe. To: Chief of Naval Operations (OP-16-Pr).

Subject: U.S. Naval Technical Mission in Europe Technical

Report No. 485-45, German Powder Composition and Internal Ballistics for Guns - Forwarding of.

Enclosures: (A) (H') Four (4) complete copies of subject report as listed in distribution.

(B) (HV) One (1) set of negatives of photographs in subject report with copy No. 5 as listed in distribution.

1. Enclosures (A) and (B) are forwarded herewith.

2. CNO (OP-16-Pr) is requested to make complete additional copies of this report for forwarding to such other agencies as may be interested.

L.V. HONSINGER Captain, U.S.N.

Acting

I Howsinger

DISTRIBUTION To:

CNO (OP-16-PT)	No.	1 - 5	4
Office of Research and Inventions Copy ComNavEu Copy	No.	7 8	
ComNavEu for Admiralty Copy BuOrd (Ro)	No.	9~	
BuOrd (Ro 2) Copy BuOrd (Ro 2a) Copy	No.	11 12	
Buord (Pr 6) Buord (Pr 6a) Copy Buord (Pr 6a)	No.	13 14	
NavTocMissu (Main Filos) Copy OSED, Washington, D.C Copy	No.	15 16	

CONFIDENTIAL

TECHNICAL REPORT No. 485-45

GERMAN POWDER COMPOSITION AND INTERNAL BALLISTICS FOR GUNS


SUMMARY

This report gives a list of propellant powder compositions for German guns from 20 mm upwards together with the internal ballistics produced in each gun. A short statement on methods of internal ballistic calculation and also on closed bomb determination of ballistic constants is included.

October 1945

U.S. NAVAL TECHNICAL MISSION IN EUROPE

-1 -



UNANMOUNCED



TABLE OF CONTENTS

	····	Page
Part I.	Introduction	3
Part II.	Measurements and Calculations	3
	 (A) Calorie Value Calculations (B) Closed Bomb Work (C) Method of Analysis of Records (D) Application to Gun Calculations (E) Special Closed Bomb Investigations. 	3 3 5 6 7
Part III.	Tables	•
	(A) Index of Abbreviations(B) German Powder Compositions.(C) German Gun Internal Ballistics	8 9: 11

Closed Bomb Work and Internal Ballistics Calculations (B) (Cont'd).

work was done in the Deutsche Waffen Munition-Fabrik research laboratory at Lübeck.

2. Apparatus Closed bombs of various capacities up to three and one-half liters were used. They were constructed with a liner and shrunk-on jacket and were tested at 30 tons/sq.in. The chamber length was usually five or more diameters. The cooling water was pumped through a water jacket from a thermostat.

The charges were loaded in much the same way as in the gun and with a similar ignition system, i.e.: gun powder with or without NC igniters. The breech end was closed by a steel cartridge case containing a percussion primer. This case was reformed after each round and had a life of about 30 rounds. (It is said that some used a mushroom head with rubber gasket).

Zeiss-Ikon piezo-electric recording sets were available at Lübeck, Düneberg and Essen. That a Lübeck was used for closed bombs, rockets and guns. Calibration was by the simple press supplied by Zeiss-Ikon and of the approximate accuracy of 2%. The set at Düneberg was similar but seldom used as a mechanical gauge was preferred. At Essen both piezo-electric and mechanical gauges were used and both considered accurate, but a special unit was made to calibrate either type of gauge in position in the closed bomb. Krupps also used a piezo-electric gauge for gun measurements both in the chamber and on the base of the projectile.

The mechanical guage used at Düneberg was quite accurate utilizing a one piece beam of flexible steel with a mirror mounted on each end and the piston from the bomb working against the center of the beam. A beam of light passed over first one mirror and then the other and thence to the sensitive paper thus giving double optical deflection. The gauge was calibrated in position by a dead weight testing machine. Waterproof recording paper was used to minimize shrinkage in processing and this error was allowed for by printing two accurate centimeter scales over the record.

All the gauges used the same piston for transmitting thrust from the gases. This protruded into a recess inside the vessel and was protected by a thimble filled with grease which formed the obturation. Its cross sectional area was 0.250 sq.cms.

- 4 -

P6.3

This Document Contains Missing Page/s That Are Unavailable In The Original Document

Closed Bomb Work and Internal Ballistics Calculations (B) (Cont'd).

In the piezo-electric sets the time-scale was provided by a flashing tube controlled by a 1000 cps tuning fork. For the mechanical gauge the time scale was provided by accurate control of the angular velocity of the drum.

By means of the thermostat the closed bomb could be fired either at normal or high temperatures but no provision was made for low temperatures.

(C) <u>Method of Analysis of Records</u>. Powders were almost invariably fired in the form of tube, strip or flake, all assumed to have constant burning surface.

For any given size of a given powder composition, measurements of force and covolume were made by firing one round at each of five or more densities of loading. Then if P Max// were plotted as a function of P max >1500 atm. would lie on a straight line. The intercept of this line on the zero pressure line gave the force constant, F, and the slope gave the co-volume N. Since no heat loss correction was applied, the values of F and N depended on the web size of the powder, F diminishing N increasing with increase in web size.

Two methods of determining the relative quickness of the powder were used, depending on the use to which the results were to be put.

The simple method assumed a linear rate of burning law and no co-volume correction. Under such circumstances the pressure must be an exponential function of the time. Times were measured at which the pressure reaches P, and Pie, where P, is some arbitrary pressure, about 1/3 of P max and e = 2.718. If T is the time interval from P, to Pie, then TP max = Y equals D/B the reciprocal of the relative quickness. The beginning and end of the pressure curve are not used because they depart from the ideal exponential curve, mainly owing to irregularities in ignition. The relative quickness obtained by this method is almost independent of the density of loading for deglycol powders. For gudol powders, however, the relative quickness diminishes at higher densities of loading and the figure used is that for which P max equals the maximum pressure to be expected in the gun.

At Essen a more elaborate analysis was used, the appropriate force and co-volume constants being used to calculate Z, the fraction of the charge burnt, at each of some 20 constants of time for which the pressure was read off the curve. Then S Pdt was plotted as a function of Z

Closed Bomb Work and Internal Ballistics Calculations (B) (Cont'd).

and the slope of the middle part of this curve, which was nearly linear, gave Y. Results varied slightly for different densities of loading and a mean value was taken.

For experimental powders log P was plotted against time, using log-arithmatic graph paper, and the curvature of the line showed whether the powder were progressive or degressive.

(D) Application to Gun Calculations. For most purposes a very simple method of gun calculation was used, similar to the old ADD method. The closed bomb figures for F and N are estimated for about the right web size. The powder was assumed to be all burnt before the shot started to move, giving a pressure

Po =
$$F/1//$$
 - N

The gas was then assumed to expand adiabatically, using a value of 2 given by:

$$F = 1 + F/(J \times cal. cal.)$$
1.2

where HJ is the mechanical equivalent of heat in the appropriate units. This adiabatic curve was then intersected by a constant pressure line P = P max (crusher) and this line together with the adiabatic line to the muzzle gave the pressure-space curve used for design purposes. A factor of 0.96 was then used to allow for rounding off the corners of the diagram in calculating the muzzle energy (W + C/3) WO². A further 3% or 5% was substracted from the muzzle energy to allow for the frictional losses with one or three driving bands respectively. This method did not involve propellant size or the position of all burnt, but gave reasonably accurate results in experienced hands.

A more elaborate method was used by Krupps in detailed design of new weapons. This used closed bomb data for force, co-volume and relative quickness and started from a shot start pressure. The co-volume correction was applied in a step by step integration.

In choosing a given solution for use it was considered that the velocity at burnt should never exceed 90% of the muzzle velocity in order to obtain reasonable regularity. This gave a minimum value for the relative

Application to Gun Calculations (D) (Cont'd).

quickness of the powder. For low performance weapons, of course, V burnt would be about 20% less than Vo.

(E) Special Closed Bomb Investigations. Three special closed bomb investigations deserve mentioning. In the first place a study of the effect of moderation on the burning properties of small arms powders was made both in the closed bomb and in the gun, at Lübeck. For chopped NC tube moderated with about 4% methyl centralite or camphor the progressiveness due to the moderation counterbalanced the degressiveness due to the shortness of the tubes, giving an effectively constant burning surface.

Secondly at Dineberg a long and detailed study was made of the effect of varying the ratio of external to hole diameter, and of tube length to hole diameter, on the burning properties of powder at various temperatures. The general conclusions reached were as follows:

- (a) The mean rate of burning increased and became more irregular when the stick length exceeded thirty times the hole diameter. The temperature coefficient also increased in the same way.
- (b) The mean rate if burning became irregular if the ratio of external to hole diameter exceeded 2.5 for powders with cal. vol 800 or 2.0 for powders with lower cal. vols. Since different factories produced powders with different ballistic properties it was necessary to lay down tolerances for hole size as well as annulus and tube length in order to obtain both the required relative quickness and temperature coefficient. This work was carried out in conjunction with gun firings.

A third investigation was the effect of atmospheric humidity on moisture content and so on ballistics, but this was done mainly by gun firings.

Other investigations included the taking of gas samples from guns or closed bombs by means of a small evacuated closed vessel placed in the chamber or screwed into the wall. This small vessel was sealed by a disc, which ruptured at a suitable high pressure and admitted the gas sample. Experiments with this apparatus showed that for Ngl, and Digl. powders the gases had approximately the calculated composition but that for gudol powders the water gas equilibrium constant was well below the theoretical value. This was believed to be due to the shortage of oxygen in such powders. The continued pressure rise is closed bombs firing Gudol powders after the

Special Closed Bomb Investigations (E)(Cont'd).

charge should be all burnt was believed to be due to completion of some gas reaction which could only proceed slowly with such powders.

A somewhat similar apparatus, in which the gases produced in a small closed bomb ruptured a disk and expanded into a larger closed bomb was used for measuring the smoke produced by various powders. In this case the large vessel was fitted with a light source and photocell.

Notes and Abbreviations to Tables.

- 1. Theoretical cal. vol. in Table I have been calculated by personnel of Armament Research Department, Woolwich, England.
- 2. Units of Force in Table I and II are tons/sq. in. per gram cent-imeter.
- 3. Additional German values not given in the British translation of these tables are included in Appendix to Tables.

4. Abbreviations:

NC Nitrocellulose T. N Nitrogen content of NC by weight. N3 Nitroglycerine DIN Diethylene glycoldinitrate Trigl Triethyleneglycoldinitrate P:Lc Nitroguanadine Akar Akardite Centra Centralite I MgO Magnesium Oxide Graph Graphite Nitronaphthalene No Hydr. Hydrocellulose DNT Dinitrotoluene Ш Mineral Jelly Phth Diamylphthalate Ephu Ethylphonylurethane Dphu Di_henylurethane

APPENDIX TO TABLES

Supplementary Data on German Powder Compositions

Powder No.	Description	German Theor. Cal.Val. Cal/gm	Specific Gas. Vol. CM3/kg.
1	Ngl. Pl. P-12.5	1198	814
2	Ngl. Bl P-12.5	1144	829
3	Ngl Blp - 11.5	1023	869
Ĭ.	Ngl. RP - 9.5	832	943
2 3 4 5 6	Ngl RP - 8	725	981
6	RP 32	719	988
7 8	Digl. BIP - 10.5	925	953
8	Digl. BIP - 10.5	916	957
9	Digl. RP - 9.5	841	970
io	Digl. RP0.3	740	994
31	Digl. RP - 8.2	717	1005
12	RP - 38	686	1019
13	RP - 38N	695	1010
14	RP - E	579	1066
15	Digl. RP - KO	571	1088
16	Digl. RP - KN	559	1055
17	Digl. RP - KOD	5 75	1052
13	Digl. RP - GO	503	1123
19	Digl. RP - GO.5	497	1108
20	RP 40	540	1078
21	RP 4CN	577	1063
22	Digl. RP-Gl.5	498	1920
23	Digl. RP - G 2.5	509	1069
24	Digl. RP - G.5	و فر	1035
25	Lep 40n	_	- House
25a	Lgp 40	en e	40-00-40
26	Gup - AO to al.3	830	993
27	GuRP - 39	713	1023
28	Gurp - 7.5	537	1100
29	GuRP - 8	736	1007

Appendix to Tables (Cont'd).

Powder No.	Description	German Theor. Cal.Val. Cal/gm	Specific Gas. Vol.
30	Gurp - KN	518	1074
31	GuRP - GO	531	1102
32	GuRP - G5	476	1051

Prepared by:

C. H. BROOKS, Lt.Comdr., USNR.

G. H. NEFF Lt., USNR

T. L. MILLER Lt., USNR

J. B. CASTNER, Technician

CENAN CEN PROPELANTS

.ov ~ n n																		
			•		Mitroglyperine Powders	Pow	4		İ					- 81	17 de	British Unite	ا%	100
			ರ ಸ		4	Alter	Centr Ma	-	1						-			
	BEJ.PJ.P-12,5 -	Ara	54.45	12.80			8		. જ						1280	79.4	4065	1297
	¥£1.M.P-12,5 -	Ara	26.X	12.75	30.55	0.25	23	So	0.10						1255	77.0	3910	1256
	#g.m.P-11;5 -	1	57.75	12.75	8.8	,	8.8	કુ	0.10						3150	74.1	3550	1159
4 . P	(HEL-R. P 9.5 -	Par A	Aray 64-33	n.%	28.71		5.75	8	0.10						8	67.3	283	8
S Kgl.	Kgl.R.P 8 -	1	67.00	11.40	26.08	1	8,	°.33	0.10						3	62.5	28	188
6 R P.	R. P. 58 or RPC/38	Marry	86. 88.	11.50	25.80	,	3.8	0.15	0.30						830	62.4	0(38	808
				2 4	N C O M C	1	Porders	-	_					-	-	-	-	
			, K	Ř	D. G. N. Aker	Aker	Operator No.0		G.	of Kn M.J.		Phth.	Kaso4 Kros	OD I		-		
Lend 7	pizi.Bl.P10,5 -	Ara	33.62	13.00	35.78	0.25	0.85	કું જ	8				1		1020	72.7	3150	1005
5	51g1.81.P10,5	Arra	¥.3	13.00	4.78	0.25	0.25	,	1				-		1020	3.0	3130	192
200	M. B. P 9,5 -	A LA	61.80	12.60	36.45	··	8	0.15	0.10						8	***	2940	933
10. 0167	Digl. R. P8-0.3	nek	68.3C	11.80	29.25	1	2°30	0.15	0.10					3	830	63.3	88 , 55	3 6
11. (Digi.a. R. R.	8. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5.	714	67.70	06°71	29°02	1	8.8	0.15	0.10						05.8 0.00	8.3	2570	8
12. 8. 7.	2. 2. 38 or RFC/38	Kert	69.45	12,20	25.30	1	8,8	0.15	0°30		<u> </u>				910	61.0	24.05	785
13. R.P. 38 H	38 18	Marry	68.72	12.20	25.03	í	1.50	0.15	0°30	\$ 8					810	7:00	8545	414
14 R. 28		777	60.55	12.00	25.95	1	3.75	0.15	0.10	2,50	(4.00 DAT.	D.R.T.	3.00 Hydr.)	J. 44.	730	55.3	21.75	638
15 014	Digita BK.Q.	Plak	64c15	8.2	27.50,	1	5,35	0.15	0.10		1.85 0.90		0 7		8	55.5	द्ध इंद्र	634 or 633
16. Digi	16. Digl.R.PK.R	riek	61.09	12.00	26.17	1	8,2	0.15	0.10		1:35	0,25		8.	230	53.8	2125	

1 -1 1

	A	1		đ	744	1	3	1		by reach	3	14			į	Peros		1
*/			***		4	1	į	į	٠ ٦	*					1	THE PERSON	, g	3
<u>~</u>		•	' 	 -					`	•	•	•	•	_	Ī.		•	7
		1	4	Æ.	Dex	1	į	000	1		# 7.	H.	d d	E S				
2 :	Mel. E. PKo-b		1	_	74.63		_	33	0,10	8	2000	(10.00 D.R.T.	•		730	55.3	28	644
	DE 1. 1. 00 -		3	_	*			ş	0.10		8	8	7_		Ş	2.5	1910	25
•	(at 14.25.)	-	<u> </u>	8	*		K.	578	0 10		8	3	8	8.8	8	30.6	1805	×.
22	(at 1. 2. 2). 7	1	2.8	8'3	3		8.	0.15	0,70		8	ş		8.8	Ş	8	1920	196 H
=	(Marke and)	\$	2	8.3	36. 33	•	8.	भु	0.10		8:5	8		3 8.	8	8,	1965	ල් ද්ර ජූ
ž:					8.3		8.	235	9.30		7:8	9.85	t	8 8	8	Š	3020	cr 6 ₂₅ ·
Y 3		F.		-			8.	R	22		•				3	3	35	5
		1			8:3	R		ors oro		8.4	2.2	1 100 Date.)	8	ì	8	95.0	20.00	63.
इंट	# \$ \$ \$ \$ \$ \$ \$	<u> </u>	E:	ลียู่ ส่วั	- 4		8:	FE	010	28	88	3	8		8	(45.0)	(1755)	3),
			4 9	_	đ	1			1	-		- 6	Š	{	2			
ź	(Ou. P 10 -	Air	30.17	8.8			_		93	-			9	î	96	68.7	28.90	- झ
23	Ou. R.P. 39		35.43	16.80	B.78	8,0	40.00 0.85		6 30		g	2				69	79.76	: 5 0+
1	(de. R. R7,5	詳	3	8	16.30		30.00 0.15		0.30				\ \	. —	8	53.5	300	3, 34,
z,	Oi. R.P		\$5.23	8.8	20.02			215	97.0		8				0	2.5		ç
ğ	Ou. R.P131-	7	30.35	8.3	16.95		용 文	0.15 0.10	220	-	8	£ 33		8	36	2,4	1885	y Og
ž	(Out R.P. 430- to 61	P. T.	5.3	8 3	16.30	g g	8.6	0.15	0.30		5.3	8.	\$ 8		730	53.1	3005	65
2	Ou. R. P 05-	1	8.3	118.00	18.25		8	0.15 0.20			4.50	•••	8		30	. 54.6	1890	

4

-

, ,

### Type Size 175.0 1170.5 1170.5 1170.5 #### Type 1170.2 1170.5 ##### Type 1170.2 1170.5 ##### Type 1170.2 1170.5 ###### Type 1170.2 1170.5 ####################################						1	G. Andrews		To the	3	A.				
		1	1		<u> </u>			8 4						Project	176
37 3. x. a, 0.a. 3. x. a, 0.a. 3. y. 3. y. <th></th> <th></th> <th>á a ·</th> <td></td> <td></td> <td></td> <td></td> <td></td> <td>1178.5</td> <td>. 25</td> <td></td> <td>3500</td> <td>28</td> <td></td> <td>* *</td>			á a ·						1178.5	. 25		3500	28		* *
37 R.P. 344 385 x 240 de 345 745 377 397 387		3					8 \$	8.	84	3.60	8	3300		EC.E.S.	**
H. R. P. Sam MON EL-Que (195) 1870 270 2 <	_						357	Ŗ	27.2	3.87	06 88	88	2000		
37 R. P. 368 180 x 1.8 (0.6 s) 135 z 1.6 (0.6 s) 130 z 1.6 (0.6 s						.635		g.	, ,	1 1	100	33.30	38	RF 18	
77				100 x 1.6/0.6	32		502		269	8	8	88	8.	R. P. 18 R.C. E. F.	
197 Digg. R. R6.2- 310 x 3/1 -320 -40 -40 1970 2.75 200 -4.8 -4.9 1970 -4.8 <th></th> <th></th> <th>4</th> <td></td> <td></td> <td></td> <td>Š.</td> <td></td> <td>1576.9</td> <td>2.35</td> <td>273</td> <td>8.</td> <td>8.</td> <td></td> <td></td>			4				Š.		1576.9	2.35	273	8.	8.		
44/87 Qu.R.B. 40.5- 315 x 2.3/1 .400 .300 55 Ref. in Secritor 56 Ref. in Secritor 57 Ref. in Secritor 58 Ref. in Secritor 59 Ref. in Secritor 50 Ref.			3	× 3/1			2	9.	28.00	2.3	8	8	88	4 P.	
55 Most in Secretion 1.6 520.5 2.63 555.6 - 5000 3600 1360 55 Most in Secretion 1.6 480.7 1.41 3795.5 - 3000 3600 1070 50 Indiana6 0.6- 310 x 3/1 .75 2.1 1.51 1.01 1075.5 5.3 8600 3300 770 A.R. 50 Indiana6 0.6- 310 x 3/1 .80 2.06 377 1.20 24/7.5 6.3 8600 3300 4.R. 50 Indiana6 0.6- 340 x 3/1 .80 2.06 .70 0.00 .70		\$ 8 8	04.2.40.5- MG.2.40.1- NG.38-7-61-	315 x 2.3/1 310 x 1.4/1 310 x 6 x 0.5		85.			ł	3	ı	ı	1	4. ·	
95 Most in Searches 1.0 420.7 1.41 3795.5 - 5000 3500 1070 90 Inglazz-6 0.6- 310 x 3/1 .795 2-1 335 11 1073.5 5.3 2800 3300 700 4.R. 90 Inglazz-6 0.6- 310 x 3/1 .900 2.06 377 121 24/7.5 6.3 2800 3300 4.R. 90 Inglazz-6 0.6- 310 x 3/1 .900 2.06 <t< td=""><th></th><th>×</th><th></th><td>revios</td><td></td><td></td><td>500.5</td><td>6.63</td><td>333</td><td>1</td><td>8</td><td>8</td><td>9</td><td></td><td></td></t<>		×		revios			500.5	6. 63	333	1	8	8	9		
50 mg.22-60.5-300 x 2.4/1 .755 2.1 335 1.1 1973-5 5.3 2500 3300 750 4.R. 50 mg.22-60.6-310 x 3/1 .900 2.06 377 1.20 2473-5 4.3 2500 3300 635 4.R. 50 mg.22-40.5-45 x 0.8 1.86 " " " " " 1.20 2473-5 4.3 2500 3300 635 4.R. 5130 2.20 2.20 2.30 2.30 2.30 2.30 3.70 0.80 " " " " 1.20 2.20 2.20 2.20 2.20 2.20 2.20 2.20		æ		nextos			480.7	3.43	3795.5	•	8	8	8		
90 males - 6 0.6 - 310 x 3/1		8.		x 2.4/1			335		1073.5	5.3	8	88	Ž.	4 보 지 보	
0.5-745 1.86 1.86 1.86 1.86 1.86 1.86 1.86 1.86	S(00/1) 96 344		9	570 × 3/1			37	1.8	24.73-5	•	88	8	ê	4 :	
.2- MERRY 0.00			90	2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		7.00	•		3	*			8	보 보	
	-		ng. 220. 2-			8.0	8	8	ŧ	*			017_	4	

7

Shoot 3

***	Chast 1							3						
W	8	1	fype Person	3 4	gradi	i i de	Iongth Ocp.	CO.D.	Shot travel	Total cap. Hiros	Treueuro Forking Denden kg/ 29.02.	Dengen Com	⇒ c ¥ k	Projective
and the same of th	7.5 cm Br.K & Stu- 6. (Tank & S.R.)	E.	4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4	90 x 0.3 15x 5.9/3 vt410 lgs-	şķ.	28988 88688	185.7	9.0	363.5	3,2	95%	90 0%	38833	Harana Ha Ha Harana Harana Harana Harana Harana Ha Ha Ha Ha Ha Ha Ha Ha Ha Ha Ha Ha Ha
,	7. Jab. Gasch. 36 (Nousteda Out)	£.	1. 114. 18. 18. 18. 18. 18. 18. 18. 18. 18. 18	2 x 3/2 20 x 3-5/1	HYREY.	2.3	8	. a	1054	5.75	0000	318	838xt	27. 80 82.
d . d						2.5	•	******					8888	(nedden
4 4	See Kals Sourchie gen)	£	1. (Mg1.M.P 2. (12.5- 5. (fm. 90 4. Mg18.3-9.5- (m. 10 gm. M	10x10x1.5 10 gm	**************************************		74 180.4 0.7 829. 256 270 the other charges.	is to	829.6	ž	8 ត		naz S	H. 15 (md)
4 E) (mg bio ch start)	₽.	1. 11gl. El. P105 50 x 0.15 E. 11gl. El. C. O.5 170 x 3/1 5. 11c. of the 2 and 3 is total	50 x 0.15 170 x 9/1 2d 3 is total	2. 4. 6. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5. 5.	5.65	5-83 288-3 - - - - - - - - - - - - - - - - - -	1.85	168G.7	8.05	3500	20	3 888	
· madida Tabba santas da magasa sala Mg	(Heery merke)	8 .	2. 75. 75. 72. 7. 2. 5. 0.4 5. 75. 75. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7. 7.	# X 0.2 # 80/30 ark 10c	98.52.5	K s s S	.010 3-5	; ;	ů n N	1	g	0%	សន៍ដីនី	غروا غروا
****				* ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ; ;		:							•	

P

2	١
W.	,

	·	!	ş					
	cti le	2/4.4 2 mm 2 mm 2 mm 2 mm 2 mm 2 mm 2 mm 2 m	H.2. 147.9 or 143.6, both n.se fuso. star 143.5.	12. 1/4.5 100c fume.	193	.	\$ - 1 1 1	500
	Protectile		7 8 2 5 7 5 7 5 7 5 7 5 7 5 7 5 7 5 7 5 7 5		કું વ	4.	M W W	BR 1/c.
	1 k	1080 H.F. 1022 1023 1023 1023 1023 1023 1023 1023	3 \$	\$\$	8 8	88	9. g	88
	Puro Desdera	3900	0058	3100	88	88	3350	8
•	Fressuro Forking Design Kg/ sq.one	3100	0098	2750	3150	230	0088	988
	Total cap.	3	23.03	83-58	8.38	3.40	29.61	ŝ
	Shot travel mms.	5501.5	3410	3375-3	5808.8	1	4159.3	950
	H Cap	6.35	25.5	3-67	7.63	2.49	3.67	8
•	Chamber Length O	836.5	321	530.7	530.7	348.7	530	8
	Shot vrt: o kgs.	O	9.75	0 1	0	9.0 4.6	9.0	90 20 20
	Oberge vrto kgre o	111999999 38855838	1.48	4 4 6 4 8 5 9 4	8. E	1.75 1.78 2.10 1.60	2.85 2.55 2.55	N.W.
	Sign	800 x 8-75/4 800 x 5-5/2 800 x 5-5/2 800 x 7/5-85 800 x 7/4-9 800 x 5/4-9 785 x 5/4-2	290 x 4.5/2 \ 290 x 4.5/2.5\ 290 x 4.9/1.8 255 x 4.4/3.2	495 x 5/2.75 or C/91495 x 55/2.75 40 490 x 4-3/1.7 480 x 4/2.4	495 x 4.35/1.5 485 x 4.5/1.5 480 x 3.3/2.8	320 x 4.2/3 320 x 4.2/3 320 x 4.2/3 300 x 3.6/1 305 x 2.5/1	500 x 4.5/1.8 495/x 5.5/2.75 460 x 5.5/2.75	740 x 4-1/1-5 740 z 4-1/1-5
	Type Ports	2004.4 31 30 30 30 30 30 30 30 30 30 30 30 30 30	(Mgl. R.P. (or R.P.C/38 148. P.40	R. P. C/38 or C/38, or C/3 or R. P. 40 LE: 2.40.	B. P. 1/38 or 11. P. C/38 T. P. 10	R. P. C/38 or B. P. C/38. or R. P. 408 Lg. P. 408.	ng. R.P. Kl ng. R. R8.2-	Out. R. K. W. Out. R. P. P. S.
	S. S. S.	8	8	8	8	8	88	3 .
\$ 369¢	g Ç	8.8 C V V V V V V V V V V V V V V V V V V	(farredoont zun) (8.8 as 8.E.C/30 (8.3 @ \$.50/32 (8.8 ca s k c/35 (6:8 cm Flak 18	8.6 - 71ak 42
331	'en	445 8+2	क्तनं व <u>्</u>	~ * * * * * * * * * * * * * * * * * * *	45.2 0	754 A	드셔츠 	* 8

2	
تنوز	

Smot 5

l'rojoc is	•		A. P. 39/:3			R.R. 1/4-1 Star 1/4-2	B.K. 14'4.4 Star 1/4.1	b	E. L. 1.4.4	
	it E.		LP.	•		A Part	E.E.	about a position of the contract of the contra	꼭 ქ ኒ	
K. V.	756	*	1000	*		88	ž. • &	ğ, ğ,	8.8	
Dest gn			3800		·	3800	3300	8	2400	
Fressure Forking Design			88			200	2850	3950	0,5%	
Total cap.	41.82					49.46	Si Si	38.15	58.15	
Shot travel mns.	9000					4616.6	3812.5	5850	5690	
4 5 #	8.8	b.	0.0	•		8.36	8	7.7	4.7	
Chamber Length C	T	*	267	*	ţ.	603.9	386.5	8	8	
Shot Wt.	5.0	8	30.16	8		ķķ	5 4. 7 4.	25.7	15.1	
a de la	3.6		3	0.5	to len	28	\$ 4 4 4 V	200 m	888	
Siso	9/8 = (Kg)	\$30 × 6/4∙5	5/1°5 = 2/3	200 x 6.1/2.5	10 to	780 x 6-8/3-8 780 x 4-5/3-5	550 x 6/3·5 550 x 6/3·5 540 x 4-4/1·7 544 x 4-4/2·6	665 x 5.6/2.2 665 x 5.6/2.2 665 x 4.2/3.2 665 x 3.7/2.5	665 x 6.25/3 665 x 5.3/1.5 665 x 6.25/3	
Type	Gu.B. P6 0 -	or Del R6 1 -	On.R. RG 0 -	- 0 9-8:2:39:0 -	double susbers	R. P. 36 Lg. P. 40	8.5 9.8 8.5 9.8 8.5.9.0 10.5.9.0	B. P. 58 B. P. 408 IG. P. 40 I.G. P. 408	Design R8.2.	
Call bear	88	8		8	ag.	105	105	20. 8 8	201 0	,
grap.	on. Er.L.43 (10.5 cm S.K. C/28(105	10.5 cm S.K. c/38	10.5 cs. s.k. c/33(10.5 cm. Flak 38 (
j	<u>ထ</u> ်					•	•	ά	ıΰ	

)

Shank 6

Project110	18. Джевер — Ввинер	*	6 7
14 K. V.	27.5 2.5 2.5 2.5 2.5 2.5 2.5 2.5 2.5 2.5 2	630 640	85 85 85 85 85 85
Arapuro king heuton kg/ cq. cm.	88 50 11. 11.	3156	3150
Towns ng the control of the control	2483.3 24.4 2500 2	2300	2700
Total cap. Miros	3 mt	26.85	٧٧٠40
Shot trayal	2483.3 10 d doo	2565	43CC.5
Cap.		3.6	7,80
Clander Length G	14.81 211.7 2.3 Total chart. 1.022 kg. ities are as follows Total chart. Total chart.	385	791.5
Shot we.	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	14.95	15-14
Charge Tre Kga	. 25.5 . 20.6 . 20.0 . 20.0	2.65 2.20	9 W IV 0 4 T. 0 IV
Stre	3 x 3 x 0.8 4 x 4 x 1.8 4 x 4 x 1.8 10x 10x 0.8 8 x 8 x 0.9 10x 10x 0.8 6 x 6 x 1 7 175 x 5.5/2	x 3/1.3 x 5.9/1.3	x 3•1/3•5 x 5•9/3•0
Tables .	1. Digl.Bl.P10.5 3 x 3 x 0.8 3. 4. 6. (plus " 4 x 1.2 1. Digl.Bl.PA 0 - 4 x 4 x 0.9 3. du. Bl.PA 0 - 4 x 4 x 0.9 5. (plus " 8 x 8 x 0.9 1. Digl.Bl.Z-10.5 10x10x0.2 2. Ms.Bl.P. 6 x 6 x 1 3. 6. (" " 8 x 8 x 0.9 2. Ms.Bl.P. 6 x 6 x 1 5. 6. Mt.R.P. 7 5. 6. Mt.R.P. 7 5. 7 6. 6 x 6 x 1 5. 7 6. 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	Digl. R.PC 0.5- 545 Kz.a.P. 545	Digl.R.P G 0.5- 450
Caltano Firs.	105	105	9
an:	1. F.E. 18 (1)ght horitant) or 1. F.H. 18 M (with name) brake)	carerate & torer! (105)	19. 5-10 cm. X-12. 22. Sorry Jun)
Permies No.	८ ०० ५ ०० ।	<u>e</u>	5. 5.

;	•
	,

::110	Se	*3 57F	
Projecti 1.	12	interer orrest and and	min mi so
ш.v. п/в		25 25 25 25 25 25 25 25 25 25 25 25 25 2	8 8. 8.
iro Dostgn cillo	3260	8	855 865 875
Pronsiuv Harking Dosign kg/ sq.cm.	2800	2600	23.50 23.00 23.00 23.00
fotal cap. litros	54.88	14.49	75.5 75.9
Shot travel mas.	501.0	38°	603
or Cap.	10.18	1.9 1.270 kg.	12,30
Charber Length Cap.	1034.5		481 619
Shot wto kgs.	15,14	-242 14-61 158 -277 -332 -437 -100) 1-170) total oh. wt. 2 in the composite of the composit	14.61 28.0 37.6
Churge irte Kgo	2.84 0.95 0.85		2.650)14.81 0.430) 8.50 28.0 5.75 37.6 5.60 "
Siro	800 x 3 ·1/1·5 350 x 5·5/2·5		260 x 2.6/1.0 60 x 2.6/1.0 630 x 8/4.25 630 x 6.4/2.1 650 x 6.5/4.5 650 x 5.6/5.6
Type	1764.8.PG 0.5- 13G: 8.P G 2-	1. Dig. B. P 10.5 10x 10x 0.2 2 2 2 3 4 x 0.6 4 x 4 x 0.6 4 4 x 4 x 0.6 4 4 x 4 x 0.6 5 2 4 2 4 x 0.6 2 4 2 4 x 0.6 2 5 4 2 4 x 0.6 2 2 4 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	
Calibro (tal)	(105	§	9 8
. ung	3. 10 cm x 16/40(105	10 cm. Gab. Ench.	# 1.0. (
Youder No.	# X	4 %	भू न्दन्द्र <u>म्</u>

S Year

Step to

	on Powder	25 cm S. 4/85	149-1	1.770 1.770 1.8.7.8.38	Stae 150 x 10/4-4 140 x 11/5.75	B.1	rig S	Longth Me.	Cap.	travel.	ittes 136.5	Activities Discovering Discovering Name of State	3730	× 8 8 .	Projectile (H.E. 1/4.4
150 1. mig. R. P.—D.5- 3 x 3 x 0.6 .178 39.0 50 1.7 1395 - 1920 2397 1399	4 • 44 	the up This KQ56 (terrescoort gus)		25.4.3. 25.4.3. 26.4.3. 26.4.3.	× 25.2	4 4 8 8 0 8	4.0 4.0	80	۶. ظ	88	123.2	3000	3500		Star 1/4.5. R.S. 1/4.6 Star 1/4.3
(150 1. Delib. B10.5-4 x 4 x 1.2 .005 364 7.22 3761 75 2500 237 250 25	a a may practical company describe an investment of the second of the se	(beary infinity Can)	8	1. Hearth P.D.	~~	eriere a garanet	ğ	8 2 3	\$ - S	26 × 40 ×	, 8 , ×	C 86	098		
		Seary Northear)	8	1. Prebala B-10.5 2	* * * 1.8 * 1.9 × 15/4	11.085 1.085 1.395 1.870 5.665	S - 53	\$	8	3761	2	250	000	######################################	B.S. 19 or 19 Eo (enti- cozcato)

Sheet 10

MARK C. C. S.	
1. Dig. R. P D. S C 200 z y y . S. 5.209	F. Indian Co. 1 1990 2 197.2 1992 1
Special ob. for rootes shall. Digital. R6. 1- 1990 x 3-4/1-3 5-600 Highla. R6. 2- 1950 x 3-4/1-3 6-0 43-0 1270 24-0 6954 144 7000 3500 635 Highla. R6. 2- 1950 x 3-4/1-3 6-0 43-0 1270 24-0 6954 144 7000 3500 635 1. Dig. M. P IA. 5- 4 x 4 x 1 x 5 1 3 3 4 3 5 5 5 10-1 4354-5 36-1 2700 3150 255 3. 1. Dig. M. P IA. 5- 4 x 4 x 1 x 5 1 3 3 4 5 5 6 6 5 10-1 4354-5 36-1 270 x 40 x 60 x 60 2 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	Special ob. for rootet that 1. Dig. R. P. O. 1 - 100 x 3.471.5 \$.000 Dig. R. P. O. 1 - 100 x 3.471.5 \$.000 Dig. R. P. O. 1 - 100 x 3.471.5 \$.000 Dig. R. P.
Digital R. G. S. (25 x 7.97).4 Med (45.0 1270 24.0 6964 144 5000 5600 695 Me R. R. Digital R. R. G. S. (25 x 7.97).4 Med (45.0 1270 24.0 12.0 12.0 12.0 12.0 12.0 12.0 12.0 12	Digl. R. P. G. 1.— 590 x 3.497.3
4 x 4 x 1.8 (*95) 43.5 505.5 10.1 4354.5 30.1 2700 3190 255 10.1 4354.5 30.1 2700 3190 255 2700 1.190 2700	4 x 4 x 1.8 (.95) 43.5 505.5 10.1 4354.9 39.1 2700 31.90 25.5 10.1 1.05 1.05 2.07 2.07
460 x 5.6/3 2.13	460 x 5.6/3 2.13
Carnetive charges for the sens velocities. High Rule - 10.5- 10 x 10 x 0.2	Carmative charges for the sens velocities. Indiana10.5-10 x 10 x 0.2
1.50 including ch. 1.535 1	1.50 including oh- 1.535 1.535

.

Short 11

Projecti le) H.E. 39	#4. 68 kgs. 		H.E. 38	A.P. 1/3	or H.S. 1/3 or 1/3.3 (to in mass fuse.) H.S. 1/4.7	1 3 C AT . TOMA		(A. P. 1/2.9) (or prectice (1/2.8 or (E.S. 1/4.5)	(113.5 kgs.
À K	8	ς, ξ,	, 	£ 3	86	575) 88	8	88	
Fressure Forking Dealer	3750	lth Plocity	Fore charge 4, put in central tube of fore charge 3 to increase velocity in norm gun. Special charge 1, total wt. 15.5 kgs., fired with min	ty W 1 to	3800		3700		3800	
	 -	fired w	of fore of	nd veloci ial char d velocit	2930		3300	the Sh	3500 2500 21001 (
Total Cap.	196.6	168. 168.	tube fran- 5.5 kg	Age and age of a series	152.5		390.6	uded 1	313.7 Bargs vo	
-	8448 8448	Fore charge 5, total wt. 9.70 kgs., fired with medn charge to give ch. wt. 28.78 kgs. and welcofty	n central in norm	dal charge 2 wrapped round special charge total charge wt. 38.98 kgs. and velocity	32.5 5007.5 152.5			stick lengths which are included in the oh. wto	1302 48.9 7524 313.7 3400 with small Service charge velocity	
HO:	12.0 12.0	3 C	put 1 locato		32.5		70.3 8845	which	48.9 7524	
Length Hand	1652.4 (22.0	harm 3,	rate to	pecial charge ive total char	200		1,062	lengths	1302 1302 /s.	
to t	in a	Fore o	Fore of		6.0	2 %	227	stick	108 or 800 a/s	
Charge To	T~~	~	ir j		2. .5	25.5 26.15	\$\$ \$0		5.75 5.0 5.0 Argas for valootty 800 n/s.	
Tomber Star	HH	060 x 7.6/3 1.5 x 1.5 000 x 60.6/65	000 x 7.673 11-5 x 11-5 200 x 7/4.8	4	1000 x 10/4.0	1000 x 9.5/3.6 1066 x 7.5/5.8	635 x 14/5	635 x 5/2 ain amil amounts	845 x 13/5 845 x 9/5.75 845 x 9/5.0 chaded charges for	
2,00	Ha.R. P. DigiR. PG 2.9-	Ns. 140. N.P. Olg1.R.PG 2.5-	Digl.& P0 2.5- No. Ma. N. P. Mel. B. P0 9-	Mg1.R.PG 9-	R.P. 0/38	E. P. 0/36	61 60	LG-P.40 (855 x 5/8) The so charges contain small amounts	R. P. C/12 or E. P. C/32 or E. P. C/36 There are also re	~ · · · · · · · · · · · · · · · · · · ·
- Sure				_	172.6		ĝ	_£'_		**************************************
Hg	17 cm K. 1/50 (17 om 8.K. 1/40(172.6		20.3 ca. c/34e p	***************************************	21 cm. S. K. L/45 20	
Powdr.	1 %	1 %	22.	•		42 29	4	3	ક્રું	*************

Chrot 12. : .

S	Collin	Type Parker	Sin	Charge at: X88	Shot wet.	Chamber Longth co	cap.	Shot travel	Total cap.	Freesure Fortag Design	Seure Dostign	K. V.	Projectile
(Norther)	002	1. Del. Re. P10.5- 8.	1.9 2 15/4	2.48	$\perp \simeq$	863.5	2.5	5436.5	200	0668	3970	252	A.S. 18 or
•				14.4°	3 x 3		olude 0. sulq	1.00 kgs 5 kgs. N	Digl.	wts. include 1.00 kgs. Digl.Bl.P10.5- x 0.6 plus .05 kgs. Ns. Man. N.P. 1.5 x 1.5	5- × 1.5	% % % % % %	E.E. 18 Be of of of the
		6. Digla. P 6 1 Alternative charges 1. On Re. P 4 1. P.	200 = 5-4/3 for the name ve	15.00 18.00		including .10 kgs. Hr. Man. K.P.	kgs. Ng	Nan K	P. 1.5	1.5 x 2.5		453 582	(Be means anti-concusts
	~~~			2 3 2 8 B	× × × × × × × × × × × × × × × × × × ×	1 0 0 X	nolude 1 plus 0,9	wts. include 1.00 kgs. Gu.Bl.PA x 0.6 plus 0.5 kgs. Hs.Man.H.P. l.	Gu.Bl.	wits. include 1.00 kgs. Gu.Bl.P4 O. z O.6 plus O.5 kgs. Hs.Man.H.P. 1.5 x 1.5.	1.5.		
7.12 (120 km. remes)	₩	Outl. PC 4-	## = 14/6	r	300.5	\$	3,	27805	1339	3 343 27805 1337 4125	480	3500	id 13
,	· ~~	plus due P G 4-	1900 × 14/4 865 × 14/4	äa	Zildra		is (main marge to	one age. (man plus ist and 2nd for fore fore othergo to increase velocity to	rt and 2 • veloo	6 3	charges)	1625	ŧ
25 cm S.K.1/40	338	R. P. 32	300 × 12/6.6	44.5			73.8	7362	405°B	200	3550	835	A.P. 1/2.6
(Reflag	` ~	or R. P. 38	100 × 18.9/6.6	65.0	## ## *					-		88	H.B. 1/4.1
	~		*			There 37.6 ar welocit	There are also 57.6 and 35.0 relocitios of,	Reall S Rgs. rea	ervice poetive	There are also small Service charges of 57.6 and 35.0 kgs. respectively to give velocities of	40	588	es acore.
% ca. S.K.1/50	<u>'</u>	R.P. 36	1000 x 30/4	65.0	(148.5	1830	0.08	9288	533.4	2800	3200	852	E.S. 1/4.2
K. 5 (30 Hz. mange)	0 7	Dig1.R.PG 3	1330 × 10/4	0.0	153.3	2008	110	10459	88	3100	2600	8	B.3. 35
	≂-	*	*	0.99	₽.				•	*****	-	880	ř
6. 28 cz. 8. Z.C/34(283	n.r. 32	1850 × 10/7	110.8	\$ 330	2619	180	11886	2.8.3	3200	3700	• 06	
	~.·	or 11. P. 38	15/4.0	114.9	~	*****				Praym-, g. g-g-			
			,				-		·.				

Shoet 13

25 cm, S.I. 1/90 245	John Wo.	Çm	. Californ	Porton		Chargo	Shot	Chamber Length Cop.		Shot	Total	Fressure	Sure De 1	> .	Pro fore 6.10
26 cm. S.L. 1/50 (2012) 2. (a) (2012) 2. (b) (2012) 3. (c. 2. 2. 3) (2012) 3. (c. 2. 2. 2. 3) (2012) 3. (c. 2. 2. 2. 3) (ġ		1 1	ķ	ŝ			.mag.	•	kg/80		19/8	
	•	26 cm. S.L. 1/50 (. 583	R. P. 32	1210 × 16/6.7	104.5	303	2182		11259	874.2	2100	00:75	3.5	(12. 17. 18. 18. 18. 18. 18. 18. 18. 18. 18. 18
25 cm 3.5 Q/20 { 250 m 3.5 Q/20 113.0 200 cm may be fixed with any projective. Both and constitution of the constitution o	٠ ٧	X (E) (Bailmy (mounting)		or R. P. 38	1810 x 16/6 830 x 16/6	105.5	Š							(
28 cm SLQV80 285	4			or 2. P. 36	1190 x 14.0/4.9	312.0	Rech .	- Thereo m	3y do f	 iv botk	th any p	ಸಂಖೋದ 14	<u>.</u>	0000	
Section Sect	ý	28 cm SK q/29 {	8		H	3.00T	8	2333		11572	80%8	3300	3700	910	(H.S. 1/4.2)
E. C. Column Co	7			or 12.12. 36	¥	303.3									
Fig. Color		26 one S.E. C/40(or short Bruso E (3) (Belliumy mounting)	Ŷ	R. P. 38	1830 x 10/4.7 1830 x 11/5.1	\$\$	350	1842		8558	670.8	3100	3300	620	a.c. 1/2.6 or H.B. 1/4.3 or E.S. 1/4.1
Street S	ž		8	ng. R.P G 5 - or plus " This gan also five		22 1 2 2 3	г. 2	2965	20.02 Kt a n	17607 ange of	1371.6 85 Km.	3200	3750	980 11.50	되
30.5 cm, S.i., { 305 R.P. 38 1340 x 14/6.7 { 122.4 405 2538 1190.3 11933 1093.8 3000 3300 855 1340 }	7		8	Dig. B. P 6 5		887	285	23.68	239.7	12800 sprox	1050.9	3200	3700	8	BE. 1/4.4
(123 405 2528 199.3 11933 " 3000 " 655 1340 × 18/8 (143 250 2493 197.5 11968 " 3350 " 1120	~	30.5 cm S.:- {	ĕ	R. P. 38	346.7 {	122.4	ភ ំនិ	25.28 24.93 24.93	199.3	11933	1093.8	3000	380	355	BE.1/3.8 ar. A.B. B.S. 1/3.6
	7				38/81	33	405 250		198.3	11933	: :	3000	r •	655 1120	12 C
			······································					rigag gendalik b. 19avil						معدد درون درون	

23	Sheet 34	-							-					
No.	8		Parket.	3450	K z g	Shot wate	Chamber Length Ca	jė š	Shot travel mas	Total cep. ligus	Torith Pa	12.8 13.8	: e E k	Zrojset II.
1 2	K. 1		3	800 × 5/3	33.4	575	1603	168.5	1881	683	2500	88	3	£23.5.4.000-
4	•		5. 5. Ne. II P. 68.5-	1000 x 9.4/5	38. 34.	4	446	1 polude	ch wts. include -4 kgs. N.P.	•	1.5 × 1.5.		38	
44	38 48 8.K C/34	8	R.P. 33 or R.P. 36	950 x 16.4/6.8 890 x 17/7	88	8	2330	310	16175	3088	3200	3700	08 020	
	Slegizied K.	8	Gu R. P6 5-	1820 × 10.5/3.5 (8.5	Ž	2479	361.7 15926	15926	27.2	03.	3700	8	Literat nood.
	(Coast defeace)			, 	g	8	296	8	15941	2	380		026	Brain ing.
25	Adolf X. (Const defence)	206.4	406.4 Gu B.R4 5-	380 × 30/3	- <u>8</u> <u>5</u>	0,00	3576	098	17074	2012	2001. 001.	3650	813 813	for the
9	Camp Ifts	3	1. ng.ba -0.5-	550 × 13/5		0201	8	135	5431	213	88	3050	369	En. C. C. State
	(Beary marter)		s * *		188	1	g. ats	include	include .5 kgs. E.P.		1.5 × 1.5	,	45. 46.	
	Ceret 36	533.4	Ou. R. P.	1	88	800	4366	1250	21674	1129	000	34.20	073	_
32.	a. Justav	8	Ge E.P. 6 %	1510 × 25/18 (000	8:	4748	3400	27352		, ,	8.	88	and colours
					888	4750	* C	B E	8 F		88		970 350	1